




Hybrid 1080P DVR

ED8008TSC



FEATURES :

- Support 8 CH 2MP@12fps Recording, 1CH 2MP@15fps
- Adopt standard H.264 high profile compression format to get high-quality video at much lower bit rate.
- Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse.
- Multi-mode recording: manual / timer / motion / sensor
- Playback: 8 CH simultaneous playback
- Search: time slice, time, event (manual, sensor, motion), tag search
- Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol and CMS supported
- Remote control via IE or CMS: preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device.
- Multi-user online simultaneously
- Authorization management, log view and device status view
- HDMI output, true high resolution display
- Supports PTZ pre-set and auto cruise, up to 255 pre-sets and 8 cruises
- Supports NAT function and QR-Code scanning by mobile phone and PAD
- Powerful smart phone & Pad surveillance with iOS and Android OS



www.alma-asia.com www.almacctv.com www.facebook.com/almacctv

COPYRIGHT BY ALMA TECHNOLOGY SDN. BHD. ALL RIGHT RESERVED

DISTRIBUTE BY :



Design and specifications are subject to change without notice.



Hybrid 1080P DVR

ED8008TSC



Model		ED8008TSC
System	Compression	H.264 High Profile
	CPU	Cortex A9 Dual Core
	OS	Embedded Linux
Video	Input	BNC*8 HD TVI, HD CVI, HD AHD, ANALOG
	IP Input / Max Solution & FPS	IPC x1, 2MP @ 30FPS, 6Mbps
	Output	1080P (1920 x 1080) : VGA x1, HDMI x1 SPOT (CVBS) : BNS x 1
Audio	Input	RCA*4
	Output	RCA*1
	2-Way Audio	Take Up Channel One Audio Input
Record	Resolution	1080P, 1080P Lite, 720P, WD1, D1, CIF
	Frame Rate (Fps)	720P 200fps (PAL) / 240fps (NTSC)
		1080P 100fps (PAL) / 120fps (NTSC)
	Bit Rate:	768Kbps ~ 8Mbps
	Mode	Manual, Timer, Motion
Play	File Management	Lock, Unlock, Reserving Time
	Playback	8CH
	Search	Time/Calendar Search Event (Motion)
	Function	Play, Pause, FF, FB, Digital Zoom
Alarm	Mode	Motion, Video Loss
	Input	4 CH
	Output	1 CH
	Triggering	Record, PTZ Move Alarm Out, E-Mail, Etc.
Network	Interface	RJ45 10M / 100Mbps x 1
	Protocol	TCP/IP, UDP, DHCP, DNS, PPPOE, DDNS
	Others	Max 10 Users Online, Dual Stream
Cellphone	OS	IPhone, Android
Port	HDD	SATA x 1, Max 6TB Each HDD
	RS485	RS485 *1, for PTZ Controller
	USB	USB 2.0 x 2, for Mouse & Backup
	Remote Controller	Optional
Others	Power Supply	DC12V
	Consumption	< 8W (Without HDD)
	Dimensions (W*D*H)	300mm x 270mm x 58mm
	Working Environment	-10~50°C, 10%~90% (Humidity)

