




2MP AIO CAMERA IR2C36-0F



FEATURES

- ✓ Image Sensor : 1/3 " OV2359
- ✓ Lens : 4mm Lens
- ✓ Resolution : 1920(H) x 1080(V) 2.0MP
- ✓ IR LEDS : 36 IR LED
- ✓ IR Distance : 35M
- ✓ OSD : Yes
- ✓ Min illumination : 0.5 Lux min. illumination
- ✓ Support : CVI, TVI, AHD & CVBS
- ✓ Protection : IP66 Weather Proof
- ✓ Power Input : DC 12V
- ✓ Power Consumption : 290mA (IR ON)



www.alma-asia.com www.almacctv.com www.facebook.com/almacctv

COPYRIGHT BY ALMA TECHNOLOGY SDN. BHD. ALL RIGHT RESERVED

DISTRIBUTE BY :



Design and specifications are subject to change without notice.



2MP AIO CAMERA IR2C36-0F

FEATURES

- ✓ Image Sensor : 1/3 " OV2359
- ✓ Lens : 4mm Lens
- ✓ Resolution : 1920(H) x 1080(V) 2.0MP
- ✓ IR LEDS : 36 IR LED
- ✓ IR Distance : 35M
- ✓ OSD : Yes
- ✓ Min illumination : 0.5 Lux min. illumination
- ✓ Support : CVI, TVI, AHD & CVBS
- ✓ Protection : IP66 Weather Proof
- ✓ Power Input : DC 12V
- ✓ Power Consumption : 290mA (IR ON)



SPECIFICATION

Image Sensor	1/3 " OV2359
Picture Elements	1920(H) x 1080(V) 2.0MP
Lens	4.0MM
LED	36 IR LEDs
IR Distance	35M
Signal Format	NTSC / PAL (1280H)
Min. Illuminat on	0.5 Lux Min. Illumination
Electronic Shutter	1/23s ~ 1/150000s
3D-DNR / 2D-DNR	Auto
Digital WDR	ON / OFF
White Balance	ATW (Default) / Manual
Auto Gain Control	0-15 Adj. (OSD Setting)
Day & Night Mode	External Control (Default) / Auto / Color / B&W
Video Setting	Contrast / Color Gain / DNR / Video Mode / DWDR
Coaxial Control (UTC)	YES (AHD, TVI, CVI, CVBS)
CDS Input Voltage	DC 1V - 18V (Wide Voltage)
OSD Language	English / Traditional Chinese / Simplified Chinese / Polish / Portuguese / Italian
Video Output	AHD / CVI / TVI / CVBS (4KV Lightning Protection)
Power Supply	DC 12V (Wide Voltage 7-23V)
Power Consumption	290mA (IR ON)
Operation Temperature	-10°C ~ +50°C (-14°F to 122°F)
Storage Temperature	-40°C ~ +60°C (-40°F to 140°F)



DAY & NIGHT



AUTO WB



SENSOR



DWDR



WEATHER PROOF



MIN. ILLUMINATION



AGC